





SYSTEM COMPRESSION SPRINGS

E 1536										E 1537										E 1538										E 1539									
 <p>FOR LIGHT LOAD Maximum deflection: 40% of L0 Colour code: green</p>										 <p>FOR MEDIUM LOAD Maximum deflection: 37.5% of L0 Colour code: blue</p>										 <p>FOR HEAVY LOAD Maximum deflection: 30% of L0 Colour code: red</p>										 <p>FOR VERY HEAVY LOAD Maximum deflection: 25% of L0 Colour code: yellow</p>									
spring rate c (N/mm)	Fn(N)	d1 Ø mm	d2 Ø mm	L0 mm	No.	spring rate c (N/mm)	Fn(N)	d1 Ø mm	d2 Ø mm	L0 mm	No.	spring rate c (N/mm)	Fn(N)	d1 Ø mm	d2 Ø mm	L0 mm	No.	spring rate c (N/mm)	Fn(N)	d1 Ø mm	d2 Ø mm	L0 mm	No.																
1.55	12.4	4.8	6	16	E 1536/ 6 x 16	4.70	30.1	4.4	6	16	E 1537/ 6 x 16	12.74	61.2	4	6	16	E 1538/ 6 x 16	33.01	105.6	3.6	6	16	E 1539/ 6 x 16																
0.97	12.1				25 E 1536/ 6 x 25	25	28.5				25 E 1537/ 6 x 25	7.74	58.0				25 E 1538/ 6 x 25	19.81	99.0				25 E 1539/ 6 x 25																
0.62	11.9				38 E 1536/ 6 x 38	1.84	28.0				38 E 1537/ 6 x 38	4.91	56.0				38 E 1538/ 6 x 38	11.92	90.6				38 E 1539/ 6 x 38																
0.50	12.6	0.6			51 E 1536/ 6 x 51	1.47	29.9	0.8			51 E 1537/ 6 x 51	3.67	56.2	1			51 E 1538/ 6 x 51	9.51	97.0	1.2			51 E 1539/ 6 x 51																
2.46	19.7	6.4	8	16	E 1536/ 8 x 16	5.38	34.4	6	8	16	E 1537/ 8 x 16	12.51	60.1	5.6	8	16	E 1538/ 8 x 16	30.85	98.7	5	8	16	E 1539/ 8 x 16																
1.56	19.5				25 E 1536/ 8 x 25	3.64	34.4				25 E 1537/ 8 x 25	6.90	51.7				25 E 1538/ 8 x 25	23.00	115.0				25 E 1539/ 8 x 25																
1.09	20.7				38 E 1536/ 8 x 38	2.41	36.7				38 E 1537/ 8 x 38	5.05	57.6				38 E 1538/ 8 x 38	13.23	100.6				38 E 1539/ 8 x 38																
0.78	19.8	0.8			51 E 1536/ 8 x 51	1.91	38.9	1			51 E 1537/ 8 x 51	4.00	61.1	1.2			51 E 1538/ 8 x 51	9.26	94.4	1.5			51 E 1539/ 8 x 51																

