

ISO 12164-1	DIN 69893	Form A	G 2.5 25000 min <sup>-1</sup>			HSC
----------------	--------------	-----------	----------------------------------	--	--	-----

### PRODUCT DESCRIPTION

- » Slim design
- » With integrated length adjustment screw
- » High clamping forces
- » Temperature resistance up to 120 °C
- » Optimal workpiece surfaces and longer service lives thanks to very good damping properties
- » With Balluff chip hole

### APPLICATION

- » For clamping tools with cylindrical shank and h6 shank tolerance
- » Use in combination with reduction sleeve enables flexible clamping
- » For drilling, reaming and milling

### INCLUDED IN THE DELIVERY

- » Includes built-in length adjustment screw, user guide and hexagon key

d2	d3	l2	l3	l4	Interface	d1	A	No.	#CU#
10	50	28	12	73	HSK-A 63	4	120	HWZ 1166/HSK-A 63/ 4/120	XX,YY
12	50	37	10	74	HSK-A 63	6	120	HWZ 1166/HSK-A 63/ 6/120	XX,YY
14	50	37	10	74	HSK-A 63	8	120	HWZ 1166/HSK-A 63/ 8/120	XX,YY
16	50	41	10	74	HSK-A 63	10	120	HWZ 1166/HSK-A 63/10/120	XX,YY
18	50	46	10	75	HSK-A 63	12	120	HWZ 1166/HSK-A 63/12/120	XX,YY

