

Page 1 of 15

Revision date: 07.03.2023

Safety Data Sheet

according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VRT 180

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol, Coating material.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Meusburger Georg GmbH &	Co KG
Street:	Kesselstrasse 42	
Place:	A-6960 Wolfurt	
Telephone: e-mail: Internet:	+43 5574 6706-0 office@meusburger.com www.meusburger.com	Telefax: +43 5574 6706-12
Responsible Department:	Dr. Gans-Eichler Chemieberatung GmbH Otto-Hahn-Str. 36 D-48161 Muenster	e-mail: info@tge-consult.de Tel.: +49 2534 41594-0 www.tge-consult.de
I.4. Emergency telephone	Poison Information Center N	lainz, Germany, Tel: +49(0)6131/19240

1.4. Emergency telephone

number:

Further Information

Safety Data Sheet according to UK-REACH Regulation

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling White mineral oil (petroleum) isopentane; 2-methylbutane

Signal word:

Pictograms:



Danger

Hazard statements H222

Extremely flammable aerosol.

Print date: 13.03.2023



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

H229 Pressurised container: May burst if heated.

Precautionary statements

· · · · · · · · · · · · · · · · · · ·	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

In use may form flammable/explosive vapour-air mixture.

2.3. Other hazards

EUH018

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture (> 0.1%) do not meet the PBT/vPvB criteria according to UK REACH. This product does not contain a substance (> 0.1%) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
EC No	GHS Classification	
REACH No		
Index No		
8042-47-5	White mineral oil (petroleum)	5 - 9,65 %
232-455-8	Asp. Tox. 1; H304	
01-2119487078-27		
78-78-4	isopentane; 2-methylbutane	< 1,36 %
201-142-8	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H224 H336	
01-2119475602-38	H304 H411 EUH066	
601-085-00-2		
and the second		

Full text of H and EUH statements: see section 16.

Specific Co	nc. Limits, M-fa	ctors and ATE				
CAS No	EC No	Chemical name	Quantity			
	Specific Conc	Limits, M-factors and ATE				
8042-47-5	232-455-8 White mineral oil (petroleum)					
	inhalation: LC mg/kg	:50 = >5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000				
78-78-4	201-142-8 isopentane; 2-methylbutane					
	inhalation: LC	;50 = > 25,3 mg/l (vapours); oral: LD50 = > 2000 mg/kg				

Further Information

Product does not contain listed SVHC substances > 0.1 % according to UK REACH.

Page 2 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration! Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. Alcohol resistant foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide (CO). Nitrogen oxides (NOx). Aldehyde.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Page 3 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

General advice

Ventilate affected area. Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Eliminate leaks immediately. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Provide adequate ventilation.

Hints on joint storage

Do not store together with: Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Page 4 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Oxidizing liquids. Oxidizing solids. Self-reactive substances and mixtures. Organic peroxides. Radioactive substances.

Infectious substances.

Further information on storage conditions

Recommended storage temperature: 10-30 °C. Do not store at temperatures over: 50 °C Note: Storage requirements for flammable aerosols.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
78-78-4	Isopentane	600	1800		TWA (8 h)	WEL

DNEL/DMEL values

Substance			
	Exposure route	Effect	Value
White mineral oil (petroleum)			
ong-term	inhalation	systemic	164,56 mg/m³
ong-term	dermal	systemic	217,05 mg/kg bw/day
_, long-term	inhalation	systemic	34,78 mg/m³
Consumer DNEL, long-term		systemic	93,02 mg/kg bw/day
_, long-term	oral	systemic	25 mg/kg bw/day
isopentane; 2-methylbutane			
ong-term	inhalation	systemic	3000 mg/m³
Consumer DNEL, long-term		systemic	643 mg/m³
Consumer DNEL, long-term		systemic	214 mg/kg bw/day
Consumer DNEL, long-term		systemic	214 mg/kg bw/day
ong-term	dermal	systemic	432 mg/kg bw/day
	White mineral oil (petroleum) ong-term ong-term ., long-term ., long-term ., long-term sopentane; 2-methylbutane ong-term ., long-term ., long-term ., long-term	Exposure route White mineral oil (petroleum) ong-term inhalation ong-term dermal ., long-term inhalation ., long-term dermal ., long-term oral ., long-term inhalation ., long-term oral ., long-term inhalation ., long-term oral	Exposure routeEffectWhite mineral oil (petroleum)ong-terminhalationsystemicong-termdermalsystemic., long-terminhalationsystemic., long-termdermalsystemic., long-termoralsystemic., long-termoralsystemic., long-terminhalationsystemic., long-terminhalationsystemic., long-terminhalationsystemic., long-terminhalationsystemic., long-terminhalationsystemic., long-terminhalationsystemic., long-termoralsystemic., long-termoralsystemic

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection

Page 5 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Page 6 of 15

Revision date: 07.03.2023

equipment.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. Suitable material: Butyl rubber. (0,5 mm) Breakthrough time >480 min

Penetration time (maximum wearing period): >160 min

The selected protective gloves have to satisfy the specifications of the Personal Protective Equipment at Work (Amendment) Regulations 2022 and the standard EN ISO 374.

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

Use only respiratory protection equipment with CE-symbol including four digit test number.

Thermal hazards

No special precautionary measures are necessary.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling po	pint and	-40 - 200 °C
boiling range:		
Flammability:		not determined
Lower explosion limits:		1,5 vol. %
Upper explosion limits:		8,5 vol. %
Flash point:		-80 °C
Auto-ignition temperature:		not determined



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Dissolution rate:	not relevant
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	not relevant
Vapour pressure:	not determined
Density (at 20 °C):	0,8 g/cm³
Bulk density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not determined
9.2. Other information	
9.2. Other information	
9.2. Other information Information with regard to physical hazard classes	
9.2. Other information Information with regard to physical hazard classes Explosive properties	sive/highly flammable mixtures may develop.
9.2. Other information Information with regard to physical hazard classes	sive/highly flammable mixtures may develop. No data available
<u>9.2. Other information</u> Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose	
 <u>9.2. Other information</u> Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: 	
 <u>9.2. Other information</u> <u>Information with regard to physical hazard classes</u> Explosive properties In case of insufficient ventilation and/or through use, explosing sustaining combustion: Self-ignition temperature 	No data available
 <u>9.2. Other information</u> Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: 	No data available not relevant
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas:	No data available not relevant
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties	No data available not relevant
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none	No data available not relevant
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics	No data available not relevant 425 °C
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics Evaporation rate:	No data available not relevant 425 °C not determined
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics Evaporation rate: Solvent separation test:	No data available not relevant 425 °C not determined not determined
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics Evaporation rate: Solvent separation test: Solvent content:	No data available not relevant 425 °C not determined not determined not determined
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics Evaporation rate: Solvent separation test: Solid content: Sublimation point: Softening point:	No data available not relevant 425 °C not determined not determined not determined not determined not determined not determined not determined
9.2. Other information Information with regard to physical hazard classes Explosive properties In case of insufficient ventilation and/or through use, explose Sustaining combustion: Self-ignition temperature Solid: Gas: Oxidizing properties none Other safety characteristics Evaporation rate: Solvent separation test: Solid content: Sublimation point:	No data available not relevant 425 °C not determined not determined not determined not determined not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Flow time:

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions. Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

not determined

Page 7 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Oxidizing agents, strong. Peroxides. Acid.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

Further information

In use, may form flammable/explosive vapour-air mixture.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
8042-47-5	White mineral oil (petrole	eum)					
	oral	LD50 mg/kg	> 5000	Rat	ECHA dossier	OECD 401	
	dermal	LD50 mg/kg	> 2000	Rabbit	ECHA dossier	OECD 402	
	inhalation (4 h) dust/mist	LC50	>5 mg/l	Rat			
78-78-4	isopentane; 2-methylbuta	ane					
	oral	LD50 mg/kg	> 2000	Rat	ECHA dossier	OECD 401	
	inhalation (4 h) vapour	LC50 mg/l	> 25,3	Rat	ECHA dossier	OECD 403	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

White mineral oil (petroleum): In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA dossier Carcinogenicity: Method: (oral.) OECD Guideline 453 (Combined Chronic Toxicity/Carcinogenicity Studies); Species: Rat; Length of test: 2 years; Result: NOAEL = 1200 mg/kg Literature information: ECHA dossier Reproductive toxicity: Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Species: Rat ; Results: NOAEL >= 1000 mg/kg Literature information: ECHA dossier Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Page 8 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Page 9 of 15

Revision date: 07.03.2023

Species: Rat; Results: NOAEL >= 5000 mg/kg Literature information: ECHA dossier

isopentane; 2-methylbutane: In vitro mutagenicity/genotoxicity Method:OECD 471 (Ames test). Result / evaluation: negative. In vivo mutagenicity/genotoxicity Method:EU Method B.12 Result / evaluation: negative. Reproductive toxicity Method: OECD 416. Species: Rat. Exposure duration: 10w. Result: NOAEC= 7000 ppm Literature information: ECHA dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

White mineral oil (petroleum): Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) Species: Rat ; Results: NOAEL = 20000 ppm. Literature information: ECHA dossier Subchronic dermal toxicity: Method: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-day Study); Species: Rat.; Results: NOAEL >2000 mg/kg Literature information: ECHA dossier

isopentane; 2-methylbutane: Subchronic inhalative toxicity Method: OECD 413. Species: Rat. Exposure duration: 90 d. Result: NOEC= >2220 ppm Literature information: ECHA dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance (> 0.1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

No data available.

SECTION 12: Ecological information



Page 10 of 15

Revision date: 07.03.2023

Safety Data Sheet

according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
8042-47-5	White mineral oil (petroleu	um)					
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Lepomis macrochirus	ECHA dossier	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	ECHA dossier	OECD 202
78-78-4	isopentane; 2-methylbutane						
	Acute fish toxicity	LC50 mg/l	4,26	96 h	Oncorhynchus mykiss	ECHA dossier	OECD 203
	Acute algae toxicity	ErC50 mg/l	1,26	72 h	Scenedesmus capricornutum	ECHA dossier	OECD 201
	Acute crustacea toxicity	EC50	2,3 mg/l	48 h	Daphnia magna	ECHA dossier	OECD 202
	Fish toxicity	NOEC mg/l	7,618	28 d	Oncorhynchus mykiss	ECHA dossier	QSAR
	Crustacea toxicity	NOEC mg/l	13,29	21 d	Daphnia magna	ECHA dossier	QSAR

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name								
	Method Value d Source								
	Evaluation		-						
8042-47-5	White mineral oil (petroleum)								
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 31,3% 28								
	Product is not easily biodegradable.								
78-78-4	isopentane; 2-methylbutane								
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 71,4 28 ECHA dossier								
	Easily biodegradable (concerning to the criteria of the OECD)								

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
8042-47-5	White mineral oil (petroleum)	> 6
78-78-4	isopentane; 2-methylbutane	4
BCF		

CAS No	Chemical name	BCF	Species	Source	
78-78-4	isopentane; 2-methylbutane	171	Pimephales promelas	ECHA dossier	

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1

%.

meusburger

Safety Data Sheet

according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

160504

Disposal recommendations

Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	EO

Page 11 of 15



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

Transport category: Tunnel restriction code: Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	2 D UN 1950 AEROSOLS 2 - 2.1
Classification code: Special Provisions: Limited quantity: Excepted quantity:	5F 190 327 344 625 1 L E0
Marine transport (IMDG) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1950 AEROSOLS 2.1 - 2.1
Marine pollutant: Special Provisions: Limited quantity: Excepted quantity: EmS:	NO 63, 190, 277, 327, 1000 mL E0 F-D, S-U
Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1950 AEROSOLS, FLA 2.1 - 2.1
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	A145 A167 A802 30 kg G Y203 E0

7, 344, 381, 959 AMMABLE 203 75 kg

Page 12 of 15

Revision date: 07.03.2023

203 150 kg



Page 13 of 15

Revision date: 07.03.2023

Safety Data Sheet

according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Refer to section 6 - 8

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

2010/75/EU (VOC): 2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III): > 80 % (640 g/l) 100 % (800 g/l) P3a FLAMMABLE AEROSOLS

Additional information

Safety Data Sheet according to UK-REACH Regulation UK Aerosols Regulation UK REACH Appendix XVII, No (mixture): 3, 40 The mixture is classified as hazardous according to GHS (GB CLP).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 1 - slightly hazardous to water

Water hazard class (D):

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: White mineral oil (petroleum) isopentane; 2-methylbutane

SECTION 16: Other information

Changes

Rev. 1,0; Initial release 05.12.2019 Rev. 2,0; Revision 07.03.2023

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labeling, Packaging DNEL: Derived No Effect Level d: day(s) EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances ECHA: European Chemicals Agency ECOSAR: Ecological Structure Activity Relationships



according to UK REACH Regulation

Print date: 13.03.2023

VRT 180

EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) IUCLID: International Uniform ChemicaL Information Database GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) OECD: Organisation for Economic Co-operation and Development PNEC: Predicted No Effect Concentration PBT: Persistent, bio-cumulative, toxic QSAR: Quantitative Structure-Activity Relationship RID: Regulation Concerning the International Transport of Dangerous Goods by Rail RTECS: Registry of Toxic Effects of Chemical Substances SVHC: Substance of Very High Concern TRGS: Technische Regeln für Gefahrstoffe **UN: United Nations** UVCB: Chemical Substances of Unknown or Variable Composition, Complex Reaction Products and Biological Materials vPvB: very persistent and very bio-cumulative VOC: Volatile Organic Compounds w: week(s)

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page 14 of 15



according to UK REACH Regulation Print date: 13.03.2023

VRT 180

Page 15 of 15

Revision date: 07.03.2023

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)